

MPN: MC-HDM19193V2.0

HDMI Cable 4K, 3m

Ultra High-Speed 4K@60Hz 18Gbit HDMI 2.0 Cable with Dynamic HDR and Audio Return Channel (ARC). Supports resolutions up to 4K and refresh rates up to 60Hz.

- HDMI 2.0 4K60Hz
- 18Gbps
- Support YUV sampling: 4:4:4
- HDCP 2.2
- Great Performance



Specifications

Features	3D	Yes
	Audio Return Channel (ARC)	Yes
	AWG wire size	30
	Bandwidth	60 MHz
	Cable jacket material	Polyvinyl chloride (PVC)
	Cable length	3 m
	Cable material	Copper
	Colour depth	16 bit
	Connector 1	HDMI Type A (Standard)
	Connector 1 form factor	Straight
	Connector 1 gender	Male
	Connector 2	HDMI Type A (Standard)
	Connector 2 form factor	Straight
	Connector 2 gender	Male
	Connector contacts plating	Gold
	Data transfer rate	18 Gbit/s
	Dolby technologies	Dolby TrueHD
	HDCP	Yes
	HDCP version	1.4/2.2
	HDMI Ethernet channel	Yes
	HDMI version	2.0
	High Dynamic Range (HDR) supported	Yes
	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
	Maximum resolution	4096 x 2160 Pixels
	Plug and Play	Yes
	Product colour	Black
	Quantity per pack	1 kusû

Features	RGB support	4:4:4
	RoHS compliance	Yes
	Supported graphics resolutions	4096 x 2160
	Supported video modes	2160p
Other features	Quantity	1
Package dimensions	Depth (package,cm)	15.9 cm
	Gross Weight (Package, kg)	0.2 kg
	Height (package,cm)	3.8 cm
	Width (package,cm)	21.9 cm
Product dimensions	Net Weight (Product, kg)	0.17 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Cable diameter	7.3 mm

Other products in this series



Cable length	Black	White
0.5	MC-HDM19190.5V2.0	MC-HDM19190.5V2.0 WH
1.0	MC-HDM19191V2.0	MC-HDM19191V2.0WH
1.5	MC-HDM19191.5V2.0	MC-HDM19191.5V2.0WH
2.0	MC-HDM19192V2.0	MC-HDM19192V2.0WH
3.0	MC-HDM19193V2.0	MC-HDM19193V2.0WH
4.0	MC-HDM19194V2.0	
5.0	MC-HDM19195V2.0	MC-HDM19195V2.0WH
7.5	MC-HDM19197.5V2.0	MC-HDM19197.5V2.0WH
10.0	MC-HDM191910V2.0	MC-HDM191910V2.0WH
15.0	MC-HDM191915V2.0	
20.0	MC-HDM191920V2.0	

Other images



Recommended accessories



Vivolink Pro DP to HDMI Adapter Ring
MPN: PROADRING1