



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL 201 TPL

DESCRIPTION

Single sided general purpose tape.

PRODUCT DATA

Backing	LDPE film laminated with cloth; available in several colours
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.180	PSTC 133
Adhesion to steel	N/25mm	14	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	15	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

General purpose single sided tape, suitable for binding of insulation covers such as pipes and panels, also fit for general use and “emergency” mending of sunshades, etc.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ Good adhesion on irregular surfaces	✓ High performance on several materials
Laminated cloth LDPE backing	✓ Highly conformable ✓ Available in a wide range of colour	✓ Suitable for several kinds of applications ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

VR001EN_REV06_201TPL

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.